

**4XEM Universal USB Power Adapter/Wall Charger for all USB devices 4port**

**4XEM PART - 4XUSBCHARGER4**



4XEM's compact 2.1 AMP 4Port USB Wall Charger will charge your iPad (including Retina display iPads) and other iDevices without the need for a separate computer. Quickly plugs into a standard household outlet for fast, efficient charging. Connect the adapter directly to your iDevice via a separate 8-Pin Lightning or 30-Pin to USB Cable connector. Also charges all iPhone/iPod models and compatible MP3 players, digital cameras, tablets, mobile phones and other devices.

Problem it solves: No need to connect your iDevice to a computer for recharging. With the Power Adapter/Wall Charger, you can easily plug into any household outlet for a quick boost! Charge up to 4 different devices simultaneously!

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    [tschaus@4xem.com](mailto:tschaus@4xem.com)



## Features:

- 4XEM unmatched lifetime warranty
- For all USB mobile phones and tablets
- For iPhones 5/5c/5s/SE/6/6 Plus/6s/6s Plus/7 7 Plus
- For iPads with Retina/ mini/mini 2/ Air/2/3/4 and Pros
- For iPods nano 7th Generation/touch 5th Gen./6th Gen.
- Output Voltage: 5V
- Maximum Output Power: 5W
- Charge up to 4 devices



## Application(s):

- Power Delivery
- Portable Charging
- Travel
- Home/Office use
- Mobile Power
- USB devices



**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    [tschaus@4xem.com](mailto:tschaus@4xem.com)



|                          |  |  |
|--------------------------|--|--|
| Warranty Information     | Warranty   | 1 year   |
| Connector(s)             | Charging Port(s)<br>Power Source   | 4x USB Type-A<br>Non-Polarized NEMA 1-15P (Standard NA Wall Outlet)<br>Removable with Retractable Prongs (Reveals Non-Polarized IEC 320 C7/C8 Connection when removed) |
| Performance              | Industry Standards   | N/A  |
| Physical Characteristics | Colour<br>Display<br>LED Indicator<br>Power Cable Length<br>Product Height<br>Product Width<br>Product Length<br>Weight of Product | White<br>No<br>Power: Red<br>N/A<br>2.45 in [62.2 mm]<br>1.41 in [29.0 mm]<br>2.29 in [58.2 mm]<br>2.93 in [74.5 mm] (with power prongs out)<br>2.40 oz [68 g]         |
| Power                    | Total Power Budget<br>Power Delivery<br>Input Voltage<br>Output Voltage  | 20W<br>N/A<br>110-240VAC, 50Hz-60Hz @ 0.5A<br>5V DC @ 2.1A   |
| Environmental            | Operating Temperature<br>Storage Temperature<br>Humidity   | 0°C to 40°C (32°F to 104°F)<br>-20°C to 80°C (-4°F to 176°F)<br>5% to 90% (non-condensing)   |
| Packaging Information    | Package Type<br>Package Height<br>Package Width<br>Package Length<br>Shipping (Package) Weight                                     | Poly-Bag<br>5.91 in [150 mm]<br>3.94 in [100 mm]<br>1.17 in [29.7 mm]<br>2.47 oz [70 g]  |
| What's in the Box        | Included in Package  | 1x 4-port USB Charger  |
| Notes                    | Notes  | Maximum power output per port is 10W.<br>Total power output cannot exceed 20W.   |

\* Product appearance and specifications are subject to change without notice.

\* Same day shipping is only available for orders shipping within the United States.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

**Contact Todd Schaus 4XEM sales Rep**  
**1-866-999-4936 Ext.104    tschaus@4xem.com**

