

4XEM USB-C 4K Triple Display Docking Station with 65W Power Delivery

4XEM Part- 4XUG39PD1



4XEM's USB-C 4K Triple Display Docking Station is a premier device able easily connect multiple displays to heighten any monitor set-ups. With two HDMI ports and a DVI/VGA port, this station is compatible with a variety of monitors. Along with its display capabilities, the 13 total ports offer an even wider range of use. Adding in the station's 65W power delivery capability it is also an incredibly effective charger. Get versatility and advanced functionality with 4XEM's 4K Triple Docking Display Station with 65W PD.

**Problem It Solves:** Display up to 3 different monitors easily and effectively, while also keeping your device fully charged. This 13-port docking station is a top-class utility device.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    [tschaus@4xem.com](mailto:tschaus@4xem.com)



## Features

- USB 3.0 (Type-A and Type-C) ports
- compatible with all USB enabled devices
- provides 65W USB power delivery to devices
- HDMI port 1 and DVI/VGA port support dual 2K display via DisplayLink Graphic
- HDMI port 2 supports up to 4K@30Hz via USB-C alt. mode
- RJ-45 Gigabit Ethernet port provides high speed wired network
- 4-Pole Phone Jack provided combo audio headset, microphone port.
- 4 x USB 3.0 downstream ports
- 2 x USB-C downstream ports

## Application

- Home theatre
- Small business
- Multi-Screen Display
- Device charging

**4XEM Products Are Available At Your Favorite Online Retailers**





**DATA SHEET**

|                          |   |  |   |
|--------------------------|---|--|---|
| Warranty Information     | Warranty  | 2 Years  |   |
| Hardware                 | 4K Support  | Yes  |   |
|                          | Displays Supported  | 3  |   |
| Connector(s)             | USB Ports   | 6  |   |
|                          | Fast-Charge Port(s)   | Yes  |   |
|                          | Network   | Yes  |   |
|                          | SD Card Reader  | No   |   |
|                          | Audio   | Yes  |   |
|                          | Host Bus Type   | USB Type-C   |   |
|                          | Power Delivery  | 65W  |   |
|                          | Lock Slot   | No   |   |
|                          | Industry Standards  | HDMI 1.2, 1.4<br>DVI-I SL<br>HDCP 1.4<br>Power Delivery (PD 2.0)<br>Battery Charging (BC 1.2)<br>DisplayLink DL3900<br>Fresco Logic FL5002<br>Genesys Logic GL3253   |   |
|                          | Chipset ID  |  |   |
|                          | Host Connector  | USB 3.0 Type-C (5Gbps)   |   |
|                          | Host Connector Cable  | Detachable   |   |
|                          | Connector Type(s)   | 1x HDMI 1.4 (10.2Gbps - Alt-Mode Required from Host)<br>1x HDMI 1.2 (4.95 Gbps)<br>1x DVI-I SL (4.95 Gbps)<br>1x USB 3.0 Type-A (5Gbps - Fast Charge)<br>3x USB 3.0 Type-A (5Gbps)<br>2x USB 3.0 Type-C (5Gbps)<br>1x RJ-45 (10/100/1000Mbps)<br>1x 4-Pole TRRS Phono Jack (Audio In/Out Combo)                    |   |
|                          | Performance   | Maximum Digital Resolutions  | HDMI 1.4: 4096 x 2160 @ 30Hz<br>HDMI 1.2/DVI-I SL: 2048x1152 @ 60Hz each<br>DVI-I (Analog Mode): 1920 x 1200 @ 60Hz |
|                          | Software  | OS Compatibility   | Windows 7, 8, 8.1, 10<br>Mac OS X<br>Chrome OS  |
| Power                    | Power Source  | AC Adaptor Included (100-240 VAC, 50/60Hz, 2A Max , CLASS II)  |   |
|                          | Power Adaptor Style   | Brick  |   |
|                          | Power Consumption   | 100W   |   |
|                          | Input Voltage   | 20V DC   |   |
|                          | Input Current   | 5A   |   |
|                          | Output Voltage  | 20V DC   |   |
|                          | Output Current  | 5A   |   |
| Power Delivery           | 65W to Host<br>35W to Peripherals   |  |   |
| Physical Characteristics | Product Height  | 8.78 in [223 mm]   |   |
|                          | Product Width   | 1.02 in [26 mm]  |   |
|                          | Product Length  | 3.15 in [80 mm]  |   |
|                          | Weight of Product   | 11.92 oz [338 g]   |   |
|                          | Color   | Black  |   |
|                          | Material  | ABS Plastic  |   |
|                          | Cable Length  | 3 ft [0.91 m]  |   |
|                          | Power Button  | N/A  |   |
|                          | Status LEDs   | Power: Blue<br>Network: Green)   |   |
|                          | Environmental   | Operating Temperature  | 0°C~40°C  |
| Storage Temperature      |   | -10~70°C   |   |
| Humidity                 |   | 10%~90%,noncondensing  |   |
| Packaging Information    | Shipping (Package) Weight   | 3.34 lbs [1.51 kg]   |   |
|                          | Package Height  | 8.82 in [224 mm]   |   |
|                          | Package Width   | 9.67 in [245.5 mm]   |   |
|                          | Package Length  | 3.84 in [97.5 mm]  |   |
| What's in the Box        | Included in Package   | 1x USB-C Triple Display Universal Docking Station<br>1x 3' USB 3.0 Type-C to Type-C Cable (E-Mark Chip)<br>1x 3' USB 3.0 Type-C to Type-A Cable<br>1x DVI to VGA Adaptor<br>1x Quick Start Guide<br>1x 20V DC/5A 100W Power Adaptor (46" fixed output cable)<br>1x NEMA 5-15P to IEC 320 C13 Power Cord (55" long) |   |
| Country of Origin        | Country of Origin   | China  |   |
| Notes                    | *When connecting to host with USB Type-A cable, only 2 monitors can be used.<br>HDMI 4K port requires HDMI Alt-Mode Support from host via USB-C connection. * |  |   |

\* Product appearance and specifications are subject to change without notice.

\* Same day shipping is only available for orders shipping within the United States.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

**Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    tschaus@4xem.com**

